



AA70 GunJet[®]

High Pressure Spray Gun

Heavy-duty industrial spray gun
**ergonomically designed and balanced
to reduce operator fatigue**

Benefits

- Engineered for long-lasting, dependable operation
- Easy trigger pull at high pressure
- High-impact nylon handle and trigger construction
- Stainless steel valve seat and ball for maximum service life
- Forged brass valve, Teflon[®] backup ring and Viton[®] O-ring seals guarantee the highest chemical resistance
- Designed with large grip area to accommodate work gloves and contour handle to comfortably fit small hands
- Vented gun housing keeps the handle cool at maximum operating temperature
- Safety lock prevents unintentional operation
- Optional weep feature prevents freezing in cold weather

Teflon is a registered trademark of E. I. du Pont de Nemours and Company

Viton is a registered trademark of DuPont Performance Elastomers, L.L.C. Corporation

Specifications

Maximum operating pressure: 5000 psi (345 bar)

Maximum flow capacity: 10 gpm (38 l/min)

Maximum operating temperature: 300° F (150° C)

Inlet connection: 3/8" NPT (F) or BSPT (F)

Outlet connection: 1/4" NPT (F) or BSPT (F)

Weight: 25 oz. (715 g)

Dimensions: 7.83" x 7.56" x 1.35" (19.9 x 19.2 x 3.4 cm)

Patent Pending

Ordering Information

A A

B

7 0

W

BSPT
Conn.

Model
No.

Weep Valve
Seat Code



For more information request

Catalog No. 25: Spray Products
for the Car Wash Industry

Data Sheet 20400: Insulated
lance extension, 18" or 36"



Specify and order standard nozzles
www.spray.com/ispray

